



PIONEER INTERTRADE

PRODUCT CATALOGUE

Sales & Service Locations in India



Head Office

301-303, "A" Wing, Durian Estate, Goregaon - Mulund Link Road, Goregaon (E), Mumbai - 400 063.
Phone : 022-6678 7700 / 6678 3162-63-64 • Fax : 022 - 6678 3161
e-mail : info@pioneerintertrade.com

We invite you to visit our website for complete information
including demonstration videos on various machines

www.pioneerintertrade.com

Drills For Steel / Concrete



**THE STRONGEST
& TOUGHEST TOOLS
IN THE MARKET.**




**Drills
with Feed spindle**

- Part No. 2 2082....
- Part No. 2 2084....
- Part No. 2 1401....
- Part No. 2 2085....
- Part No. 2 2089...
- Part No. 2 2506...
- Part No. 2 2502....



Picture : Drills 2 1289 0030: Automatics Stop Twist Throttle

0010
Lever
Throttle



0030
Automatic stop
twist throttle



The last four figures of the Part No. are used to identify to the throttle type.
PLEASE SPECIFY WHEN ORDERING.

Drills with D-Handle
(for use in underground mining)

- Part No. 2 1310 0010
Geared chuck 13 mm dia.
- Part No. 2 1310 0020
Quick-release chuck 13 mm dia.
- Part No. 2 1311 0010
Morse Taper 1



Picture : Drill 2 1310 0010: internal Value Latch

Corner Drills

- Part No. 2 1602 0030
- Part No. 2 1701 ...
(for use in underground mining)
- Part No. 2 1801
(for use in underground mining)
- Part No. 2 1807
- Part No. 2 2104 0030



Picture : Hydraulic corner Drill 2 180610

Type	mm	mm	mm	mm	Nm	rpm	kW	m ³ /min	mm	mm	mm	mm	mm	kg	mm
Drills with D-Handle															
2 1310 0010	f	13	13		9	650	0.60	0.68			314		41	5.7	R3/8"m 13
2 1310 0020	f	13	13		9	650	0.60	0.68			314		39	5.7	R3/8"m 13
2 1311 0010	Mt1	f	15	13		9	650	0.60	0.68		281		41	5.4	R3/8"m 13

Direction of rotation: f = forward, r = reversible

Type	mm	mm	mm	mm	Nm	rpm	kW	m ³ /min	mm	mm	mm	mm	mm	kg	mm		
Drills with feed spindle																	
2 1401	MT 2	f	20	17		18	325	0.60	0.68	248	180	405	50	27	5.0	R3/8"m 13	
2 2084	MT 2	f	23	17		46	200	1.00	1.20	414		671	40	55	10.5	R3/4"m 15	
2 2085	MT 2	f	23	17	30	16	46	250	1.00	1.20	414		671	40	55	12.0	R3/4"m 15
2 2082	MT 3	f	32	26		46	200	1.00	1.20	433		671	40	55	11.0	R3/4"m 15	
2 2089	MT 3	f	32	26	30	16	46	250	1.25	1.50	424		671	40	55	12.5	R3/4"m 15
2 2506	MT 3	f	32	26	50	32	82	220	1.85	2.00	300	215	675	65	60	14.5	R3/4"m 15
2 2506	MT 4	f	50	32	65	40	225	80	1.85	2.00	335	252	675	65	69	17.0	R3/4"m 15

Direction of rotation: f = forward, r = reversible

Type	mm	mm	mm	mm	Nm	rpm	kW	m ³ /min	mm	mm	mm	mm	mm	kg	mm		
Corner Drills																	
2 1602 0030	MT 1	f	15	12		10	500	0.50	0.60	140	115	320	45	25	3.1	R3/8"m 13	
2 1701	MT 2	f	23	17		48	270	1.33	1.40	160	117	530	35	30	8.5	R3/4"m 13	
2 1801	MT 3	f	32	26		72	260	1.92	1.80	190	155	570	43	36.5	11.5	R3/4"m 15	
2 1807	MT 3	f	32	26		72	260	1.92	1.80	190	155	570	43	36.5	9.4	R3/4"m 15	
2 2104 0030	MT 4	f	55	50	50	40	116	180	2.20	2.00	252	205	605	55	40	17.0	R3/4"m 19

Direction of rotation: f = forward, r = reversible

Type	mm	mm	mm	mm	Nm	rpm	kW	m ³ /min	mm	mm	mm	mm	mm	kg	mm
Corner Drill, Hydraulic															
2 1806 0010	MT 3	f	32	26		121	220	2.80		190	155	550	43	36.5	11.2

Connection : Quick coupling 1/2"FF"

Oil pressure : 140 bar

Requested oil flow : 15-50 l/min