



# PIONEER INTERTRADE

## PRODUCT CATALOGUE

### Sales & Service Locations in India



#### Head Office

301-303, "A" Wing, Durian Estate, Goregaon - Mulund Link Road, Goregaon (E), Mumbai - 400 063.  
Phone : 022-6678 7700 / 6678 3162-63-64 • Fax : 022 - 6678 3161  
e-mail : info@pioneerintertrade.com

We invite you to visit our website for complete information  
*including demonstration videos* on various machines

[www.pioneerintertrade.com](http://www.pioneerintertrade.com)



**THE  
STRONGEST  
&  
TOUGHEST  
TOOLS  
IN THE  
MARKET.**



## ROTARY HAMMER DRILLS

### Pneumatic Powered SDS-plus shank

#### Model 2 2404 0010

Use: Drilling in concrete, masonry and natural stone, as well as drilling in wood and steel.

#### Model 2 2408 0010

suitable for underground mining

#### Model 2 2404 0040

for underwater use (with exhaust air connection)



Pneumatic Rotary Hammer Drill 2 2404 0010

### Pneumatic Powered SDS-max shank

#### Model 2 2414 0010

Use: Drilling and chiseling in concrete, masonry and natural stone. Drilling in wood and metal.

#### Model 2 2415 0010

for underwater use (with exhaust air connection)



Pneumatic Rotary Hammer Drill 2 2414 0010

### Hydraulic Powered SDS-plus shank

#### Model 2 2406 0010

Use: Drilling in concrete, masonry and natural stone, as well as drilling in wood and steel.



Hydraulic Rotary Hammer Drill 2 2406 0010

### Hydraulic Powered SDS-max shank

#### Model 2 2407 0010

Use: Drilling and chiseling in concrete, masonry and natural stone. Drilling in wood and metal.

#### Model 2 2410 0010

for underwater use



Hydraulic Rotary Hammer Drill 2 2407 0010



## TECHNICAL SPECIFICATION

Performance data at an operating pressure (flow pressure) of 6 bar

Type	Tool Shank	Free Speed rpm	Motor Power kW	Blows per Minute bpm	Drilling Capacity mm	Air Consumption m <sup>3</sup> /min	Length Incl. Drill Chuck mm	Weight kg	Air Connection	ID of Hose mm
<b>Pneumatic Rotary Hammer Drills</b>										
2 2404 0010	SDS-plus	420	0.50	3000	25 concrete	0.60	410	6.3	R1/2" F	10
2 2408 0010	SDS-plus	420	0.50	3000	25 concrete	0.60	410	9.5	Rd 32 x 1/4"	10
2 2404 0040	SDS-plus	420	0.50	3000	25 concrete	0.60	410	6.6	R1/2" F	10
2 2414 0010	SDS-max	250	1.20	2500	32 concrete / 80 masonry	1.50	495	11.9	R1/2" F	13
2 2415 0010	SDS-max	250	1.20	2500	80 masonry	1.50	495	11.9	R1/2" F	13

<b>Hydraulic Rotary Hammer Drills</b>										
2 2406 0010	SDS-plus	625	0.60	4460	25 concrete		475	8.2	(without hoses)	
2 2407 0010	SDS-max	250	1.30		32 concrete / 80 masonry		495	13.0	(without hoses)	
2 2410 0010	SDS-max	250	1.30		80 masonry		495	13.0	(without hoses)	

<b>Hydraulic:</b>	<b>Connection:</b>	Quick Couplings 1/2" FF
	<b>Oil Pressure:</b>	100 bar
	<b>Oil Flow:</b>	10 - 50 l/min

### Rotary Hammer Tools

#### Drill Bits, SDS-plus Shank, 10 mm Diameter

Part No.	Diameter x Overall Length mm	Spiral Length mm	Part No.	Diameter x Overall Length mm	Spiral Length mm	Part No.	Diameter x Overall Length mm	Spiral Length mm
9 2513 1550	5 x 160	100	9 2513 1610	12 x 160	100	9 2513 1680	20 x 300	250
9 2513 1560	6 x 160	100	9 2513 1620	12 x 260	200	9 2513 1700	22 x 250	200
9 2513 1570	8 x 160	100	9 2513 1630	14 x 160	100	9 2513 1710	22 x 450	400
9 2513 1580	10 x 160	100	9 2513 1640	14 x 260	200	9 2513 1730	25 x 250	200
9 2513 1590	10 x 260	200	9 2513 1660	16 x 300	250	9 2513 1740	25 x 450	400

When drilling over 500 mm, drill a pilot hole with a shorter bit of the same diameter.

#### Drill Bits, SDS-max Shank, 18 mm Diameter

Part No.	Diameter x Overall Length mm	Working Length mm	Part No.	Diameter x Overall Length mm	Working Length mm	Part No.	Diameter x Overall Length mm	Working Length mm
9 2513 1810	12 x 340	200	9 2513 1890	20 x 320	200	9 2513 1960	40 x 370	250
9 2513 1820	12 x 540	400	9 2513 1900	20 x 520	400	9 2513 1970	40 x 570	450
9 2513 1830	14 x 340	200	9 2513 1920	24 x 320	200	9 2513 1980	45 x 570	450
9 2513 1840	14 x 540	400	9 2513 1930	24 x 520	400	9 2513 1990	50 x 570	450
9 2513 1850	16 x 340	200	9 2513 1940	30 x 370	250			
9 2513 1860	16 x 540	400	9 2513 1950	30 x 570	450			

When drilling over 500 mm, drill a pilot hole of at least 150 mm with a shorter bit of the same diameter.

#### Chisels, SDS-max Shank, 18 mm Diameter

Part No.	Description	Length mm	Width mm	Part No.	Description	Length mm	Width mm
9 2507 3510	Pointed Chisel	400	-	9 2507 3520	Flat Chisel	400	24
9 2507 3530	Flat Chisel	360	50	9 2507 3540	Spade Chisel	300	80

#### Accessories

9 2902 0200	Drill Chuck	9 2902 0210	Adapter SDS
-------------	-------------	-------------	-------------