



PIONEER INTERTRADE

PRODUCT CATALOGUE

Sales & Service Locations in India



Head Office

301-303, "A" Wing, Durian Estate, Goregaon - Mulund Link Road, Goregaon (E), Mumbai - 400 063.
Phone : 022-6678 7700 / 6678 3162-63-64 • Fax : 022 - 6678 3161
e-mail : info@pioneerintertrade.com

We invite you to visit our website for complete information
including demonstration videos on various machines

www.pioneerintertrade.com

• PNEUMATIC

• HYDRAULIC



DRILLS / IMPACT DRILLS / ROTARY HAMMER DRILLS

DRILLS

| Order No. | Drill chuck (geared chuck) mm | Free speed rpm | Power kW | Drilling capacity concrete masonry mm | Connection mm | Hose I/D mm |
|------------------|-------------------------------------|----------------------|-------------|---|------------------|-------------------|
| PNEUMATIC | | | | | | |
| 2 1267 0010 | 10 | 1550 | 0,5 | 10 | R 1/4" | 10 |
| 2 1268 0010 | 13 | 850 | 0,5 | 13 | R 1/4" | 10 |

IMPACT DRILL

| Order No. | Drill chuck (geared chuck) mm | Free speed 1/min | Power kW | Drilling capacity concrete masonry mm | Connection mm | Hose I/D mm |
|------------------|-------------------------------------|------------------------|-------------|---|------------------|-------------------|
| PNEUMATIC | | | | | | |
| 2 1266 0010 | 13 | 950 | 0,5 | 13 20 | R 1/4" | 10 |

Performance data at an operating pressure of 6 bar (cont. flow),
0,6 m³/min air consumption

ROTARY HAMMER DRILLS

| Order No. | Adapter | Free speed 1/min | Blows per minute 1/min | Power kW | Drilling capacity concrete masonry mm | Connection mm | Hose I/D mm |
|---------------------------|----------|------------------------|------------------------------|-------------|---|------------------|-------------------|
| PNEUMATIC | | | | | | | |
| 2 2404 0040 ¹⁾ | SDS-plus | 420 | 3000 | 0,5 | 25 | R 1/2"female | 10 |
| 2 2417 0010 ²⁾ | SDS-max | 250 | 2500 | 1,2 | 32 80 | R 1/2"female | 13 |

Performance data at an operating pressure of 6 bar (cont. flow),
1,5 m³/min air consumption

| Order No. | Adapter | Free speed rpm | Blows per minute rpm | Power kW | Drilling capacity concrete masonry mm | Connection mm | Hose I/D mm |
|------------------|----------|----------------------|----------------------------|-------------|---|------------------|-------------------|
| HYDRAULIC | | | | | | | |
| 2 2406 0010 | SDS-plus | 625 | 4460 | 0,6 | 25 | 3/4"-16UNF | |
| 2 2418 0010 | SDS-max | 250 | 2500 | 1,3 | 32 80 | 3/4"-16UNF | |

Performance data at an operating pressure of 100 bar (cont. flow),
oil flow 10-50 l/min

IMPACT WRENCHES / CORE DRILL

IMPACT WRENCHES

| Order No. | for Bolts up to mm | Square drive kW | Tightening torque (hard thread*) Nm | Hose I/D mm | Connection |
|------------------|--------------------------|-----------------------|---|----------------|--------------|
| PNEUMATIC | | | | | |
| 6 1315 0060 | M 30 | 1" | 1350 | 13 | R 1/2"female |
| 6 1315 0070 | M 30 | 3/4" | 1350 | 13 | R 1/2"female |

Performance data at an operating pressure of 6 bar (cont. flow),
1,7 m³/min air consumption

IMPACT WRENCH

| Order No. | for Bolts up to mm | Square drive kW | Tightening torque (hard thread*) Nm | Hose I/D mm | Connection |
|------------------|--------------------------|-----------------------|---|----------------|------------|
| HYDRAULIC | | | | | |
| 6 1514 0010 | M 27 | 1" | 1650 | 12 | M18x1,5 |

Performance data at an operating pressure of 140 bar (cont. flow),
15-38 l/min oil flow (adjustable)

IMPACT WRENCH

| Order No. | for Bolts up to mm | Square drive kW | Tightening torque (hard thread*) Nm | Hose I/D mm | Connection |
|------------------|--------------------------|-----------------------|---|----------------|------------|
| HYDRAULIC | | | | | |
| 6 1520 0010 | M36 | 1" | 3400 | 16 | M18x1,5 |

Performance data at an operating pressure of 140 bar (cont. flow),
25-45 l/min oil flow (adjustable)

CORE DRILL

| Order No. | Drilling capacity mm | Free speed rpm | Power kW | Torque Nm | Connection |
|------------------|----------------------------|----------------------|-------------|--------------|------------|
| HYDRAULIC | | | | | |
| 2 1317 0030 | 160 | 380 / 900 / 1800 | 2,8 | 60 / 38 / 17 | 1/2"FF |

Performance data at an operating pressure of 140 bar (cont. flow),
22 l/min oil flow

SAWS / AXIAL GRINDER

CHAIN SAW

| Order No. | Length of bar usable mm | Overall length mm | Air consumption m³/min | Power kW | Connection |
|------------------|-------------------------------|-------------------------|------------------------------|-------------|--------------|
| PNEUMATIC | | | | | |
| 5 1022 0020 | 430 | 790 | 2,9 | 3,0 | R 3/4"female |

Performance data at an operating pressure of 6 bar (cont. flow),
2,9 m³/min air consumption



RECIPROCATING SAWS

| Order No. | Valve type | Stroke mm | Number of strokes rpm | Power kW | Connection |
|------------------|---------------|--------------|-----------------------------|-------------|------------|
| HYDRAULIC | | | | | |
| 5 1220 0010 | Twist | 60 | 500 | 2,8 | 12S |
| 5 1220 0050 | Lever | 60 | 500 | 2,8 | 12S |

Performance data at an operating pressure of 140 bar (cont. flow),
oil flow 15 l/min



SABRE SAWS

| Order No. | Cutting capacity Wood mm | Stroke Steel mm | Number of strokes rpm | Power kW | Connection | Hose I/D mm |
|------------------|--------------------------------|-----------------------|-----------------------------|-------------|--------------|-------------------|
| PNEUMATIC | | | | | | |
| 5 1217 0010 | 160 | 19 | 28 | 1,3 | R 1/2"female | 13 |

Performance data at an operating pressure of 6 bar (cont. flow),
1,3 m³/min air consumption

| Order No. | Cutting capacity Wood mm | Stroke Steel mm | Number of strokes rpm | Power kW | Connection | Hose I/D mm |
|------------------|--------------------------------|-----------------------|-----------------------------|-------------|----------------|-------------------|
| HYDRAULIC | | | | | | |
| 5 1219 0010 | 160 | 19 | 28 | 1,5 | M18x1,5 female | 12 |

Performance data at an operating pressure of 140 bar (cont. flow),
oil flow 22 l/min

